



Multiraster

THE ADVANTAGES OF MULTIRASTER®

- Simple and quick to lay using pre-assembled pieces of almost 1 m²
- Easy to handle and install with a unique and simple click system on all sides
- Fitted with eyes to anchor the grid and thus ideal for slopes and banks
- User-friendly and quick to lay (at about 100-150 m² per hour)
- Lightweight (approximately 850 grams per piece)
- Extremely stable, even under high loads (approximately 250 tonnes per m²)
- Versatile in their use and fillable with many materials
- Optimum growing conditions due to a large cavity volume
- Recoverable surface for planting almost 100%
- Preserves the microclimate and habitats of micro-organisms
- Perfect protection against erosion
- Ideal protection for roots and bark
- Always passable, no slipping or sagging
- UV and frost resistant
- Multirasters maintain their shape, even under temperature fluctuations
- Fully recyclable
- Tested by leading institutions

Plastic grass/gravel grids may not be laid locked up

www.kremersbv.nl
T: +31 (0)46 4008676

info@kremersbv.nl
F: +31 (0)46 4580221



Multiraster

Multiraster®
Environmentally friendly ground reinforcement

Applications

- Car parks, parking spaces and driveways
- Entrances and exits
- Playgrounds and gardens
- Hiking trails in parks and public gardens (safer and more stable for walking frames and wheelchairs)
- Helipads and glider-runways
- Embankment and shore reinforcement
- Roads and paths in swampy areas and nature reserves
- Temporary hardening of surfaces during events
- Dike reinforcement
- Drivable lawns
- Recreation areas
- Holiday parks and campsites
- Zoos and animal parks
- Sports fields
- Golf courses
- Menageries
- Tennis courts
- Connecting paths and byways
- Spectator (standing) areas

Parking marker

- Size: 95 x 60 mm (2)
- Material: PP (Polypropelene)
- Color: White (Glow in the Dark is possible too)
- Note: The slots at the bottom of the cap fix the marker into place. It will not break when circular motion is applied.
- There are four click-connections at the bottom to finalize fixation.



Parking markers are available.



Multiraster® specificaties

- Material: HDPE from recycled plastics (environmentally friendly and UV-resistant)
- Colours: Black (green, grey and white on request)*
- Dimensions: Approx. 58.5 x 39.0 x 3.8 cm (L x W x H)
- Click system: Quadrilateral provided with fixed, unique, connections
- Surface area per grid: Approximately 0.228 m²
- Loading capacity: Approximately 250 ton per m²
- Weight per grid: Approximately 850 gram
- Number of grids per m²: 4.38 Pieces
- M² per pallet: 54.8 m²
- Grids per pallet: 240 Grids
- Layers per pallet: 60 Layers
- M² per layer: 0.913 m²
- Grids per layer: 4
- Packaging: Europallet 80 x 120 cm

Multiraster® is certified by Copro and suitable for normal duty, B/C, applications.

* Please note, products made from recycled materials can have variations in color and size.